

AMENDMENTS TO THE CLAIMS

The listing of claims will replace all prior versions and listing of claims in the application.

LISTING OF THE CLAIMS

Claim 1. (Cancelled)

Claim 2. (Currently Amended) ~~Rear-view mirror according to Claim 1, wherein the second drive means further comprises~~ A vehicle rear view mirror comprising:

a casing that contains an entrance sealed by a mirror;

a first drive means for pivoting said mirror on a first axis, wherein said first drive means has a first cylindrical member rotatably mounted and having a first ramp defining a closed loop having a high point and a low point situated in diametrically opposite positions;

a second drive means for pivoting said mirror on a second axis perpendicular to the first axis, wherein said second drive means has a second cylindrical member ~~rotary~~ rotatably mounted and containing a second ramp defining a closed loop having a high point and a low point situated in two diametrically opposite positions; and two second followers bearing on the second ramp in two locations situated in diametrically opposite positions, said two second followers extend in a direction perpendicular to that of the first followers, wherein said two second followers move along said second ramp when the second cylindrical member is driven in rotation by the electric motor

an electric motor for selectively driving said first and second drive means in rotation;

two first followers bearing on said first ramp in said first drive means at two locations situated in diametrically opposite positions and moving along said first ramp when said first cylindrical member is driven in rotation by said electric motor; and

two second followers bearing on said second ramp of said second drive means and two locations situated in diametrically opposite positions, said two second followers extending in a direction perpendicular to that of said first followers, wherein said second followers move along said second ramp when said second cylindrical member is driven in rotation by said electric motor.

Claim 3. (Original) Rear view mirror according to Claim 2, wherein the followers further comprise rollers resting on the ramps and carried by clamps projecting on the back face of the mirror.

Claim 4. (Currently Amended) Rear view mirror according to Claim 2, wherein the first and second cylindrical members are coaxial.

Claim 5. (Currently Amended) Rear view mirror according to Claim 4, further comprising ~~[[the]]~~ an axial opening ~~[[of]]~~ on the first cylindrical member ~~contains~~ containing a first part having ~~[[in]]~~ a cross section the same dimensions as those of ~~[[the]]~~ an axial opening of the second cylindrical member, and a second part of said axial opening of said first cylindrical member having ~~[[in]]~~ a cross section ~~dimensions~~ dimension larger than those of the first part and in which the second cylindrical member is received.

Claim 6. (Original) Rear view mirror according to Claim 5, further comprising angularly equidistant teeth having a radial face formed in the interior surface of the first part of the axial opening of the first member and in the interior surface of the axial opening of the second member, the teeth of the first member having an orientation opposite that of the teeth of the second member.

Claim 7. (Original) Rear view mirror according to Claim 5, wherein the first ramp is arranged in the interior surface of the second part of the axial opening of the first cylindrical member, while the second ramp is arranged in the exterior peripheral surface of the second cylindrical member.

Claim 8. (Original) Rear view mirror according to Claim 3, wherein the clamps projecting on the back face of the mirror extend in an annular space arranged between the first and second cylindrical members.

Claim 9. (Original) Rear view mirror according to Claim 2, wherein the first and second cylindrical members are preferably identical and placed coaxially one after the other in opposite positions.

Claim 10. (Original) Rear view mirror according to Claim 9, further comprising angularly equidistant teeth having a radial face formed in the interior surface of the openings of the first and second cylindrical members.

Claim 11. (Original) Rear view mirror according to Claim 9, wherein the first and second ramps made in the exterior peripheral surfaces of the first and second cylindrical members each define a closed loop having a high point and a low point situated in two diametrically opposite positions, followers bearing on said ramps respectively in two locations situated in diametrically opposite positions and moving along them when the cylindrical members are driven in rotation by the electric motor.

Claim 12. (Original) Rear view mirror according to Claim 11, wherein the followers are carried by clamps projecting on the back face of the mirror and extending along exterior peripheral surfaces of the first and second cylindrical members, following an axial direction.

Claim 13. (Currently Amended) ~~Rear view mirror according to Claim 1, further comprising~~ A vehicle rear view mirror comprising;

a casing that contains an entrance sealed by a mirror;

a first drive means for pivoting said mirror on a first axis;

a second drive means for pivoting said mirror on a second axis perpendicular to said first axis;

an electric motor for selectively driving said first and second drive means in rotation, having a first drive means with a first cylindrical member rotatably mounted and containing a first ramp defining a closed loop having a high point and a low point situated in two diametrically opposite positions and two first followers bearing on the first ramp in two locations situated in diametrically opposite positions and moving along the first ramp when the first cylindrical member is driven in rotation by the

electrical motor; and

a coupling device connected to the electric motor, wherein said coupling device is inserted in ~~the openings of the first and second cylindrical members~~ an opening formed in said first cylindrical member, and contains on its lateral surface first pawls oriented in one direction and ~~second pawls oriented in the opposite direction, the first pawls engaging solely with the teeth of one of the annular members~~ a plurality of teeth formed on said first cylindrical member when the electric motor drives the coupling device in rotation in one direction, ~~while the second pawls engage solely with the teeth of the other annular member when the electric motor drives the coupling device in rotation in the opposite direction.~~

Claim 14. (Currently Amended) Rear view mirror according to Claim ~~[[1]]~~ 2, wherein the first and second drive means and the control means are housed in a cylindrical receptacle situated inside the casing and containing a back provided with openings through which the clamps, projecting on the rear face of the mirror, extend.

Claim 15. (Cancelled)

Claim 16. (Currently Amended) ~~Rear view mirror according to Claim 15, A~~
vehicle rear view mirror comprising:

a casing that contains an entrance sealed by a mirror;

a first drive means for pivoting the mirror on a first axis;

a second drive means for pivoting said mirror on a second axis perpendicular to
the first axis;

an electric motor for selectively driving the first and second drive means in
rotation, wherein the first drive means has a first cylindrical member rotatably mounted
and containing a first ramp defining a closed loop having a high point and a low point
situated in two diametrically opposite positions and two first followers bearing on the
first ramp in two locations situations in diametrically opposite positions and moving
along said first ramp when the first cylindrical member is driven in rotation by the
electric motor;

a circuit mounted to said electric motor, said circuit having a current inverter
enabling said electric motor to operate bi-directionally, wherein the circuit of the motor
includes ~~two potentiometers, each~~ a potentiometer containing a conductive track and
a sliding contact, the conductive ~~tracks~~ track being situated on the ~~opposite faces~~ face
of a fixed support ~~inserted between the first and second~~ adjacent said first cylindrical
members member, while the sliding ~~contacts are~~ contact is respectively integral with
these members said cylindrical member, several positions of the sliding ~~contacts~~
contact corresponding to selected adjustment positions of the mirror being memorized.

Claim 17. (New) A vehicle rear view mirror comprising:

- a casing that contains an entrance sealed by a mirror;
- a first drive arrangement for pivoting said mirror on a first axis, wherein said first drive arrangement has a cylindrical member rotatably mounted and having a first ramp defining a closed loop having a high point and a low point situated in diametrically opposite positions;
- a second drive arrangement for pivoting said mirror on a second axis perpendicular to the first axis;
- an electric motor for selectively driving said first and second drive arrangements in rotations; and
- two followers bearing on said first ramp in said first drive arrangement at two locations situated in diametrically opposite positions and moving along said first ramp when said first cylindrical member is driven in rotation by said electric motor.

Claim 18. (New) The rear view mirror according to claim 17 wherein said second drive arrangement has a second cylindrical member rotatably mounted and containing a second ramp defining a closed loop having a high point and low point situated in two diametrically opposite positions.

Claim 19. (New) The rear view mirror according to claim 17, wherein the first and second cylindrical members are coaxial.

Claim 20. (New) The rear view mirror of claim 18, further comprising an axial opening on the first cylindrical member containing a first part having a cross-section the same dimensions as those of an axial opening of the second cylindrical member, and a second part of said axial opening of said first cylindrical member having a cross-section dimension larger than those of the first part and in which the second cylindrical member is received.

Claim 21. (New) The rear view mirror according to claim 18 wherein the first and second cylindrical members are preferably identical and placed coaxially one after the other in opposite positions.

Claim 22. (New) The rear view mirror according to claim 17 wherein the electric motor is mounted to a circuit having a current inverter enabling said electric motor to operate in two directions.